

ELMARK[®]

The Brand of Electricity

96GRF1 SERIES



GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 9W;18W;24W;36W
- ∴ Colour temperature: 3000K;4000K
- ∴ Colour body: GRAY
- ∴ Material: Aluminium+Tempered glass
- ∴ Beam angle: 15°, 30°, 45°
- ∴ CRI: Ra≥80
- ∴ Protection level against moisture and dust: IP67

FEATURES »

- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ High degree of protection
- ∴ Lightweight construction



PRODUCT DETAILS »

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	IP	Efficiency Lm/W
96GRF1/915220W	9	800	3000	67	89
96GRF1/915220	9	800	4000	67	89
96GRF1/91524WW	9	800	3000	67	89
96GRF1/91524	9	800	4000	67	89
96GRF1/1830220W	18	1600	3000	67	89
96GRF1/1830220	18	1600	4000	67	89
96GRF1/183024WW	18	1600	3000	67	89
96GRF1/183024	18	1600	4000	67	89
96GRF1/2445220W	24	2100	3000	67	87
96GRF1/2445220	24	2100	4000	67	87
96GRF1/244524WW	24	2100	3000	67	87
96GRF1/244524	24	2100	4000	67	87
96GRF1/3645220W	36	3200	3000	67	89
96GRF1/3645220	36	3200	4000	67	89
96GRF1/364524WW	36	3200	3000	67	89
96GRF1/364524	36	3200	4000	67	89

