


LAMP PHOTOMETRIC REPORT

MODEL: 99PFM602430/WH		
POWER: 24W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2655.6 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	993.0	984.9	981.7	982.4	989.4	989.5	991.6	991.8	0- 10	95.42	95.42	3.59
20	930.9	913.8	902.8	909.6	923.7	923.8	922.8	927.7	10- 20	270.1	365.5	13.8
30	832.9	806.4	790.1	800.5	823.2	820.3	816.3	825.6	20- 30	400.7	766.2	28.9
40	707.3	676.0	655.8	669.0	696.8	692.2	685.4	697.8	30- 40	470.1	1236	46.6
50	564.0	531.0	511.0	524.4	553.6	548.8	541.1	554.0	40- 50	473.5	1710	64.4
60	411.0	379.7	361.5	374.1	401.9	398.1	391.0	402.0	50- 60	416.1	2126	80.1
70	255.9	229.0	214.1	225.1	249.7	247.8	241.9	249.8	60- 70	310.5	2436	91.7
80	111.6	90.03	80.49	88.58	108.1	108.0	103.5	107.6	70- 80	176.8	2613	98.4
90	1.301	0	0	0	1.522	0	0	0	80- 90	42.54	2656	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

H(β) Range:-90 - 90DEG
 H(β) Interval: 2.0DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:
 Test Date:29 November 2022

V(B) Range:-85 - 85DEG
 V(B) Interval: 2.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.265m [K=1.0000]
 Remarks:

V(B) Range:-85 - 85DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-85 - 85DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-85 - 85DEG
V(B) Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks: